

ConneX1

ConneX1 Wireless Single Gas Detector

INSTRUMENT SPECIFICATIONS	
SIZE	4.5 x 2.95 x 1.44 in / 11.4 x 7.5 x 3.65 cm
WEIGHT	0.33 lb / 0.15 kg
OPERATING TEMPERATURE	4°F to +122°F / -20°C to +50°C (normal operation)
STORAGE TEMPERATURE	-40°F to +140°F / -40°C to +60°C
HUMIDITY (NON-CONDENSING)	20 to 90% relative humidity continuous; 0 to 95% relative humidity intermittent
ALARMS	Visual, Vibrating, Audible (95 dB), Low, High, STEL, TWA
TYPICAL BATTERY LIFE	2 years
BATTERY RUN TIME	14 hours
BATTERY RECHARGE TIME	5 hours
DISPLAY	Monochrome display 1.73 in W x 1.29 in H / 44 mm W x 33 mm H with 2 color back light modes
RATINGS EMI/RFI	NA: FCC & Industry Canada EU: Complies with EMC Directive and R&TTE Directive
CERTIFICATIONS AND APPROVALS	cCSAus: Class I, Div. 1, Gr. A, B, C, D T4 NA: AEx ia IIC T4 North America: FCC Title 47 Part 15 Class B Subpart C Intentional Radiator, Industry Canada RSS-210 ATEX: II 1 G Ex ia IIC T4 Ga IECEX: Ex ia IIC T4 Ga CE: European Conformity
WARRANTY	Full two year warranty on detector and sensors
CONNECTOR	IR
ANTENNA	Single
DATA RATES	802.11b: Up to 11 Mbps 802.11g: Up to 54 Mbps
RF OUTPUT POWER	802.11b: +18 dBm 802.11g: +18 dBm
RF RECEIVE SENSITIVITY	802.11b: -85 dBm @ 1Mbps 802.11g: -85 dBm @ 1Mbps
FREQUENCY BAND	2.400 to 2.4835 GHz (US, Canada, EMEA)
CHANNELS	USA/Canada: 14 channels
SECURITY PROTOCOLS	WPA2 PSK
SENSOR	
MEASURING RANGE	
OXYGEN (O ₂)	0 to 25% by volume
HYDROGEN SULFIDE (H ₂ S)	0 to 200 ppm
CARBON MONOXIDE (CO)	0 to 500 ppm
SULFUR DIOXIDE (SO ₂)	0 to 50 ppm



For more information

www.honeywellanalytics.com
www.raesystems.com

Europe, Middle East, Africa

Life Safety Distribution GmbH
Javastrasse 2
8604 Hegnau
Switzerland
Tel: +41 (0)44 943 4300
Fax: +41 (0)44 943 4398
gasdetection@honeywell.com
Customer Service:
Tel: 00800 333 222 44 (Freephone number)
Tel: +41 44 943 4380 (Alternative number)
Fax: 00800 333 222 55
Middle East Tel: +971 4 450 5800 (Fixed Gas Detection)
Middle East Tel: +971 4 450 5852 (Portable Gas Detection)

Americas

Honeywell Analytics Distribution Inc.
405 Barclay Blvd.
Lincolnshire, IL 60069
USA
Tel: +1 847 955 8200
Toll free: +1 800 538 0363
Fax: +1 847 955 8210
detectgas@honeywell.com

RAE Systems by Honeywell
Phone: 408.952.8200
Toll Free: 1.888.723.4800
Fax: 408.952.8480

Asia Pacific

Honeywell Analytics Asia Pacific
7F SangAm IT Tower
434, Worldcupbuk-ro, Mapo-gu,
Seoul 03922,
Korea
Tel: +82 (0) 2 6909 0300
Fax: +82 (0) 2 2025 0328
India Tel: +91 124 4752700
analytics.ap@honeywell.com

Technical Services

EMEA: HAexpert@honeywell.com
US: ha.us.service@honeywell.com
AP: ha.ap.service@honeywell.com

www.honeywell.com