



RAE Systems, Inc.
1339 Moffett Park Dr.
Sunnyvale, CA 94089 USA

Telephone 408-752-0723
Tube Orders 1-888-723-8823
Web www.raesystems.com

Gas Detection Tube Data Sheet

Hydrogen Sulfide H₂S No. 10-103-50

	Extended Range	Extended Range	Standard Range
Range (ppmv)	0.5 - 10%	1 - 20%	2 - 40%
No. of Pump Strokes	2	1	0.5
Sample Volume (mL)	200	100	50
Sample Time (min)	2 x 1.5	1.5	1.5
Correction Factor	0.25	0.5	1

Precision (Relative Standard Deviation)*: ≤ ± 10%

Linearity with No. of Pump Strokes: r² = 0.999

Humidity: No effect 5 - 85% RH

Temperature Range: 0 - 40°C
(32 - 104°F)

Temp (°C/°F)	0/32	10/50	18/64	40/104
Corr. Factor	0.75	1.0	1.0	1.0

Storage Life: 2 years in darkness at 5 - 25°C (40 - 77°F). Refrigeration preferred.

Color Change: Light Blue → Black

Reaction Principle: H₂S + CuSO₄ → CuS + H₂SO₄

<u>Cross-sensitivity:</u> Substance	Concentration (ppmv)	Apparent Reading*
CO	250	0
CO ₂	5%	0
NO	100	0
NH ₃	10%	3.5% (blue)
CH ₄	2.5%	0
SO ₂	10	0
Isobutylene	100	0
Hexane	100	0
Benzene	100	0
Toluene	100	0

*Data based on RAE pumps and tubes used in standard range.

Other Possible Interferences: Mercaptans. No response to sulfides.

Note: Time measurement to exactly 1.5 minutes for best accuracy.

Caution: Dispose of spent or expired tubes according to local regulations.
Possibly hazardous materials are given under the section Reaction Principle.